

# Status API

API Routine: APINSTAT

Parameters: UGNLPARM, UAPLSTAT

The Status API allows users to add, modify or display (retrieve) information about a particular status. The following functions are valid:

- A Add status.
- D Display status (Retrieve).
- M Modify an existing status.

This chapter covers the following topics:

- Local Data Area UAPLSTAT
  - Status API Return Codes
- 

## Local Data Area UAPLSTAT

The fields to be passed to the API as the second parameter are in the supplied local data area UAPLSTAT. The following is a detailed description of these fields:

Field Name	Format	Description
STATUS	A32	Name of the Status.
STATUS-TYPE	A2	Type of the Status. Valid Status types are:
		A      Archive
		C      Control
		D      Development
		H      History
		I      Incorporation
		M      Maintenance
		P      Production
		R      Retire
		T      Test
FUSER-DBID	N5	Database ID number where the application is located.
FUSER-FNR	N5	File number where the application is located.
FDIC-DBID	N5	Database ID number where the XREF information is located.
FDIC-FNR	N5	File number where the XREF information is located.
XREF	A1	Local or remote XREF.
MOD-TIME	T	Date and time status was last modified.
MOD-BY	A8	User that last modified status.
MOD-TID	A8	Terminal that last modified status.
ADD-TIME	T	Date and time status was added.
ADD-BY	A8	User that added status.
ADD-TID	A8	Terminal that added status.
NOTES	A60 (1:3)	Comments.

## Status API Return Codes

7250 Status exists.

7251 Status not found.

7253 Status added.

7254 Status has been modified.